

## ELECNC 1325



Stone



Aluminium



Copper

### Product Features

1. Entire steel frame structure, high temperature to make the frame regain the same steel feature of high strength, ensure the bed undeforable.
2. Gantry movement style structure, scientific and reasonable table design. Optional automatic oil lubrication system, free maintenance.
3. The X-axis and Y-axis are transmitted by the imported gear and rack with high precision. Running more stable and quiet with high speed and great power.
4. The Z-axis is driven by the ball bearing screw rod with original screw nut of European brand. Its travel is up to 120mm.
5. The large-scale straight-liner square guiding track is imported from Taiwan with high steel feature.

### Technical Parameters:

MODEL	ELECNC 1325 STONE ROUTER
Working Area	1300*2500*200
Running Speed	Upto 50m/min (Depend upon material thickness)
Spindle Moter	3KW / 4.5KW / 6KW / 7.5KW / 9KW , Spindle
Spindle Speed	0-18000 RPM / 0-24000 RPM / 0-36000
Operating System	NK 105 or Rich Auto Controller System
Drive System	Lead Shine Drive With Stepper Motor
Z MAXFeed - in	120mm (Customizable)
Holding	T - Slot
Optional Device	Dust collector (Single or Double Bag )
Command Code	Gcode (*uoo, *nc, *mmg, *plt)
Applied Material	Acrylic, MDF, Hard Wood, PVC, Aluminium, Brass, Korean, Granite
Oil supply system	Automatic Oil supply system